

GOLDEN SEASON PTE. LTD.

www.goldenseason.com.sg | www.gseason.com



Mobile shelters

Model A - C Series

Golden Season Pte Ltd

31 Playfair Road Singapore 367993 (Golden Season building) T 65.6863 2228 F 65.6363 2478
Email: info@goldenseason.com.sg Website: www.goldenseason.com.sg | www.gseason.com Co. Regn No: 03734/1984E
GST Registration No. M2-0067495-2



Shelter Models 1A to 2A series

All shelters have in built window sets, cable inlets, air con / heating duct ports, ceiling and wall hooks. Insulation liners are optional and recommend with usage of ECU sets (heating and cooling).

Shelters come complete with push poles, wind lines, stakes, groundsheet, carrier bag and repair kit.

A Series Models	
	<p>1A model</p> <ul style="list-style-type: none"> - 4.7m X 4.7m deployed. - Dome shaped, - 60kgs weight including insulation liner. - 2 to 3 persons to deploy - Can interconnect with other A series models
	<p>1AT model</p> <ul style="list-style-type: none"> - 3m X 4.7m deployed with one open side. - 52kgs weight including insulation liner - 2 to 3 persons to deploy - Can serve as a doorway to a B series shelter, and connect to other A series models.
	<p>2A model</p> <ul style="list-style-type: none"> - 5.8m X 4.7m deployed. - Dome shaped, - 80kgs weight including insulation liner. - 3 to 4 persons to deploy - Can interconnect with other A series models



Shelter Models 2AT to 4A series

A Series Models	
<p style="text-align: center;">Isometric View</p>	<p>2AT model</p> <ul style="list-style-type: none"> - 4.2m X 4.7m deployed with one open side. - 72kgs weight including insulation liner - 3 to 4 persons to deploy - Can serve as a doorway to a B series shelter, and connect to other A series models.
<p style="text-align: center;">Isometric View</p>	<p>3A model</p> <ul style="list-style-type: none"> - 7.1m X 4.7m deployed. Dome shaped, - 100kgs weight including insulation liner. - 4 to 5 persons to deploy - Can interconnect with other A series models
<p style="text-align: center;">Isometric View</p>	<p>3AT model</p> <ul style="list-style-type: none"> - 5.3m X 4.7m deployed with one open side. - 92kgs weight including insulation liner - 4 to 5 persons to deploy - Can serve as a doorway to a B series shelter, and connect to other A series models.
<p style="text-align: center;">Isometric View</p>	<p>4A model</p> <ul style="list-style-type: none"> - 8.3m X 4.7m deployed. - Dome shaped, - 120kgs weight including insulation liner. - 6 to 8 persons to deploy - Can interconnect with other A series models




Shelter Models 4AT - 6A models

A Series Models	
	<p>4AT model</p> <ul style="list-style-type: none"> - 6.6m X 4.7m deployed with one open side. - 112kgs weight including insulation liner - 6 to 8 persons to deploy - Can serve as a doorway to a B series shelter, and connect to other A series models.
	<p>5A model</p> <ul style="list-style-type: none"> - 9.5m X 4.7m deployed. Dome shaped, - 140kgs weight including insulation liner. - 8 persons to deploy - Can interconnect with other A series models
	<p>5AT model</p> <ul style="list-style-type: none"> - 7.82m X 4.7m deployed with one open side. - 132kgs weight including insulation liner - 8 persons to deploy - Can serve as a doorway to a B series shelter, and connect to other A series models.
	<p>6A model</p> <ul style="list-style-type: none"> - 10.5m X 4.7m deployed. Dome shaped, - 160kgs weight including insulation liner. - 8 to 10 persons to deploy - Can interconnect with other A series models



Shelter Models 6AT, B Series and 1C models


A Series Models



6AT model

- 9m X 4.7m deployed with one open side.
- 152kgs weight including insulation liner
- 8 to 10 persons to deploy
- Can serve as a doorway to a B series shelter, and connect to other A series models.


B Series Models



B series shelter

- 6 X 5 X 2.3m
- Very popular model due to useable area.
- Can be deployed with 4 persons.
- Weight: 110kgs with insulation liner
- Can connect to all models to form large deployment area.
- Using 1AT models, a blackout entrance vestibule can be created.
- Can be made larger or smaller as per request

C Series Models



1C model

- 4m X 4m deployed. Hut shaped,
- 55kgs weight including insulation liner.
- 2 to 3 persons to deploy
- Can interconnect with other C series models



Shelter Models 1CT to 3C Series

C Series Models	
	<p>1CT model</p> <ul style="list-style-type: none"> - 2.8m X 4m deployed. Hut shaped, - 45kgs weight including insulation liner. - 3 to 4 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule
	<p>2C model</p> <ul style="list-style-type: none"> - 5.6m X 4m deployed. Hut shaped, - 75kgs weight including insulation liner. - 3 to 4 persons to deploy - Can interconnect with other C series models
	<p>2CT model</p> <ul style="list-style-type: none"> - 4.35m X 4m deployed. Hut shaped, - 65kgs weight including insulation liner. - 3 to 4 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule
	<p>3C model</p> <ul style="list-style-type: none"> - 7.1m X 4m deployed. Hut shaped, - 95kgs weight including insulation liner. - 4 to persons to deploy - Can interconnect with other C series models



Shelter Models 3CT to 5CT series

C Series Models	
	<p>3CT model</p> <ul style="list-style-type: none"> - 5.8m X 4m deployed. Hut shaped, - 85kgs weight including insulation liner. - 3 to 4 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule
	<p>4C model</p> <ul style="list-style-type: none"> - 8.6m X 4m deployed. Hut shaped, - 115kgs weight including insulation liner. - 5 to 6 persons to deploy - Can interconnect with other C series models
	<p>4CT model</p> <ul style="list-style-type: none"> - 7.4m X 4m deployed. Hut shaped, - 105kgs weight including insulation liner. - 5 to 6 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule
	<p>5C model</p> <ul style="list-style-type: none"> - 10.2m X 4m deployed. Hut shaped, - 135kgs weight including insulation liner. - 7 to 8 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule



Shelter Models 5CT to 6CT series

C Series Models	
	<p>5CT model</p> <ul style="list-style-type: none"> - 8.9m X 4m deployed. Hut shaped, - 125kgs weight including insulation liner. - 7 to 8 persons to deploy - Can interconnect with other C series models - Can serve as doorway and vestibule
	<p>6C model</p> <ul style="list-style-type: none"> - 11.7m X 4m deployed. Hut shaped, - 155kgs weight including insulation liner. - 8 persons to deploy - Can interconnect with other C series models
	<p>6CT model</p> <ul style="list-style-type: none"> - 10.5m X 4m deployed. Hut shaped, - 145kgs weight including insulation liner. - 8 persons to deploy - Can interconnect with other C series models

Note: The insulation liner is an additional canvas layer to create an air pocket between the exterior and interior of the shelter. This serves to bring down temperature in the shelter. This is essential with the usage of Mobile Environmental Control Units. Without this layer, the cost and weight per shelter can be reduced significantly. Number of persons to deploy each shelter will also reduce.